



SMF5V0A

SOD-123FL Transient Voltage Suppressors Diode

SOD-123FL 瞬态电压抑制二极管

1. Description 描述

The TVS diode encapsulated in a small SOD-123FL Surface-Mounted Device (SMD) plastic package.

这种 TVS 瞬态电压抑制二极管采用小型 SOD-123FL 表面贴装（SMD）塑料封装。

2. Features 特性

Feature 特性	Description 描述
Peak Pulse Power Dissipation 峰值脉冲耗散功率	$P_{pk} = 200W$
Low Leakage Current 低漏电流	$I_R < 200\mu A$
ESD 静电放电	ESD 30KV Air, 30KV contact 静电释放电压：30KV 空气放电与 30KV 接触放电
Applications 应用	• Personal digital assistants 个人数码助手 • Handhelds and notebooks 手持式笔记本 • Portable devices 桌面设备 • Digital cameras 数码相机
Environmental Compliance 环保合规	• Totally Lead-Free & Fully RoHS Compliant. 完全无铅和符合 RoHS 标准^[1] • Halogen and Antimony Free, "Green" Device. 无卤素和无锑，“绿色”器件^[2]
Automotive Compliance 汽车合规	Qualified according to AEC-Q101 and recommended for use in automotive applications. 通过了 AEC-Q101 认证，推荐用于汽车电子应用场景。


[1] No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
无铅，完全符合欧盟标准 2002/95/EC（RoHS），2011/65/EU（RoHS 2）和 2015/863/EU（RoHS 3）。

[2] Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
无卤素和无锑的“绿色”产品指溴含量<900ppm，氯含量<900ppm（溴+氯总含量<1500ppm）和锑化合物含量<1000ppm。



3. Mechanical Data 封装数据

Feature 特性	Description 描述
Package 封装	SOD-123FL
Moisture Sensitivity Level 湿敏感度等级	J-STD-020 MSL1
Material 材料	Molded Plastic, “Green” Molding Compound; UL Flammability Classification Rating 94V-0. 模塑塑料封装，“绿色”成型复合材料；UL 易燃等级 94V-0。
Dimensions 尺寸	3mm × 1.9mm × 1mm body 封装本体（不含引脚）尺寸为 3mm × 1.9mm × 1mm
Terminals Compliance 引脚合规	2 terminals, Tin Plated Leads, Solderable per MILSTD-202, Method 208②③ 2 个镀锡引脚，可焊性符合 MIL-STD-202 标准中 208 方法 e3 条款的要求
Weight 重量	0.0169 grams (Approximate) 约 0.0169 克
Polarity 极性	See Diagrams Below 具体极性见下图



4. Ordering Information 订购信息

Part Number	Compliance	Package	Reel Size (inches)	Tape Width (mm)	Quantity Per Reel
SMF5V0A	Automotive	SOD-123FL	7	8	3000

5. Marking Information 丝印信息

Part Number	Marking Code
SMF5V0A	AE



6. Absolute Maximum Ratings($T_a = + 25^{\circ}\text{C}$) 绝对最大额定值

Characteristic 特性	Symbol 符号	Value 值	Unit 单位
Peak Pulse Power Dissipation 峰值脉冲耗散功率	P_{pk}	200	W
Reverse Stand-off Work Voltage 反向工作电压	V_{RWM}	5	V
Peak Pulse Current 峰值脉冲电流	I_{PP}	21.7	A
Forward Voltage $I_F = 40A$ 正向电压	V_F	2.5	V

7. Thermal Characteristics($T_a = + 25^{\circ}\text{C}$) 热特性

Characteristic 特性	Symbol 符号	Value 值	Unit 单位
Thermal Resistance From Junction To Ambient 结到环境的热阻	$R_{\theta JA}$	125	$^{\circ}\text{C}/\text{W}$
Junction Temperature 结温	T_J	-55 ~ +150	$^{\circ}\text{C}$
Storage Temperature 储藏温	T_{stg}	-55 ~ +150	$^{\circ}\text{C}$

8. ESD Ratings($T_a = + 25^{\circ}\text{C}$) ESD 评级

Characteristic 特性	Symbol 符号	Standard 标准	Value 值	Unit 单位
Air Discharge 空气放电	V_{ESD}	IEC 61000-4-2	± 30	KV
Contact Discharge 接触放电	V_{ESD}	IEC 61000-4-2	± 30	KV
Electrostatic Discharge-Human Body Model (ESD HBM) 人体放电模型	-	H3B	>8000	V



9. Electrical Characteristics($T_a = + 25^{\circ}\text{C}$) 电特性

Characteristic 特性	Symbol 符号	Min. 最小值	Typ. 典型值	Max. 最大值	Unit 单位	Conditions 条件
Breakdown Voltage 击穿电压	V_{BR}	6.4	-	7.1	V	$I_T = 10mA$
Reverse Leakage Current 反向漏电流	I_R	-	-	200	μA	$V_R = V_{RWM}$
Clamping Voltage 钳位电压	V_C	-	-	9.2	V	$I_{PP} = 21.7A$

10. Typical Electrical Characteristics Curve 典型电特性曲线




Figure1. Peak Pulse Power Derating Curve




Figure2. Pulse Derating Curve




Figure3. Pulse Wave Form





Figure4. Maximum Non-repetitive Peak Forward Surge Current

11. Package Outline Dimensions 封装外形尺寸


SOD-123FL



Symbol 符号	Millimeters 毫米	
	Min.最小值	Max.最大值
A	1.75	1.95
B	0.80	1.10
C	2.60	2.90
D	3.55	3.75
E	0.95	1.15
F	0.55	0.85
G	0.12	0.20
H	0.02	0.05



12. Suggested Pad Layout 推荐焊盘布局



Dimensions 尺寸	Millimeters 毫米
P1	3.90
P2	1.90
Q1	1.00
Q2	1.50

Fig. Soldering footprint for SOD-123FL

图 SOD-123FL 的引脚焊接



Important Notice 重要通知

Jingpeng Hulan(‘ JPHL ’) company make no warranty of any kind,express or implied,with regards to any information contained in this document.Including,but not limited to, the implied warranties of the accuracy, completeness, merchantability, or non-infringement of third party intellectual property rights.

京鹏沪连公司(以下简称“JPHL”)对本文件包含的所有信息不提供任何明示或默认的担保,包括但不限于关于信息的准确性、完整性、适销性,以及不侵犯第三方知识产权的默认保证。

The Information contained herein is for informational purpose only and is provided only to illustrate the operation of JPHL products described herein and application examples. JPHL does not assume any liability arising out of the application or use of this document or any product described herein.

本文件内容仅作信息参考,仅用于说明文中所述 JPHL 产品的操作方法及应用示例。JPHL 不承担因应用或使用本文件或本文件中描述的任何产品而产生的任何责任。

JPHL reserves the right to make changes to information published in this document, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

JPHL 保留随时修改本文件已发布信息,且不另行通知,本文件将取代并替换其发布前提供的所有相关信息。

All referenced brands, product names, service names and trademarks are the property of their respective owners.

本文提及的所有品牌、产品名称、服务名称和商标,均归属其各自所有者。



Contents 目录

1. Description 描述	1
2. Features 特性	1
3. Mechanical Data 封装数据	2
4. Ordering Information 订购信息	2
5. Marking Information 丝印信息	2
6. Absolute Maximum Ratings($T_a = +25^{\circ}\text{C}$) 绝对最大额定值	3
7. Thermal Characteristics($T_a = +25^{\circ}\text{C}$) 热特性	3
8. ESD Ratings($T_a = +25^{\circ}\text{C}$) ESD 评级	3
9. Electrical Characteristics($T_a = +25^{\circ}\text{C}$) 电特性	4
10. Typical Electrical Characteristics Curve 典型电特性曲线	5
11. Package Outline Dimensions 封装外形尺寸	6
12. Suggested Pad Layout 推荐焊盘布局	7
Important Notice 重要通知	8

© JPHL. 2025. All rights reserved

For more information, please visit: www.jphl-semi.com

For business cooperation, please send an email to: sales@jphl-semi.com

Date of release: 26 Dec 2025

©京鹏沪连. 2025. 版权所有

想了解更多信息，请访问 www.jphl-semi.com

商务合作请发送电子邮件至 sales@jphl-semi.com

发布日期: 2025-12-26
